



## UTIMACO's High Performance HSM – Taking Crypto Processing to the Next Level.



UTIMACO u.trust Anchor Se15k/Se40k

When data processing goes high speed, your HSM shouldn't be the limiting factor.

That's why UTIMACO came up with a **high-performance variant of the u.trust Anchor platform.**

It combines the flexibility and security of the industry proven SecurityServer with the processing power of UTIMACO's latest hardware. **Experience transaction processing at an unknown speed!**

### Use Cases

- High Frequency Transaction Processing
- Bulk Invoicing
- Mass Certificate Signing
- Ticketing
- High Speed Attestation

### Application Programming Interfaces (APIs)

- PKCS#11
- Microsoft Crypto API (CSP)
- Microsoft Cryptography Next Generation (CNG)
- Microsoft SQL Extensible Key Management (SQLEKM)
- Java Cryptography Extension (JCE)
- UCAPI – UTIMACO Crypto API

### Cryptographic Algorithms

- RSA, DSA, ECC with NIST and Brainpool curves
- DH, ECDH with NIST and Brainpool curves
- 5G, Block-Chain and PQC ready
- SHA-1, SHA-2 and SHA-3 Family
- AES, Triple DES, DES
- EC-VRF
- Hash-based deterministic RNG (NIST SP800-90B, AIS31 DRG.4)
- True random number generator (AIS31 PTG.2)

### Security Classification / Certifications

- FIPS 140-2 Level 3\*
- FIPS 140-3\*\*
- Common Criteria EAL4+ (eIDAS)\*\*
- PCI – HSM\*

### Features

- "m of n" authentication
- Configurable role-based access control and separation of duties
- Multi-slot support
- Remote Management
- Software Simulator for evaluation and integration testing
- Secure key storage and processing
- Windows and Linux support
- Broad ecosystem of integrations (PKI software, database encryption, ...)

### Performance (options)

- Se15K: 15000 RSA 2K sigs/s
- Se40K: 40000 RSA 2K sigs/s

### Product Family and Simulator Availability

- Based on u.trust Anchor
- SecurityServer
- Simulator included

\* in progress, \*\* planned



19 inch Network Appliance

## Reliability

### MTBF

- 134,250 hours, in acc. with Telcordia Issue 3, temperature 30°C, environment Ground Benign

## Connectivity

### Connection

- 2 RJ45 1 Gb/s network interfaces
- 2 SFP+ 10 Gb/s network interfaces as optional extension

## Certification/Compliance

### Safety

- UL, IEC/EN 60950-1
- CE, IEC/EN 62368-1
- CB Certificate

### Emissions

- FCC Class B

### Environmental

- RoHS II

## Physical Specifications

### Form Factor

- 19" Rack-mountable (1U)

### Weight

- 10 kg

### Dimensions

- Width: 446 mm (excluding brackets)
- Height: 44 mm
- Depth: 533,4 mm (excluding handles)

## Operating Environment

### Temperature

- +10°C to +50°C (+50°F to +122°F)

### Relative Humidity

- 10% to 95% Non-condensing

## Electrical and Heat Specifications

### Power Supply

- Redundant field-replaceable
- 2 x 100 ~ 240 V AC, 50 ~ 60 Hertz, 300 W

### Heat Dissipation

- Max. 222 BTU/h



PCIe Card

## Reliability

### MTBF

- 389,797 hours, in acc. with Telcordia Issue 3, temperature 30°C, environment Ground Fixed, temperature 50°C for parts in potting material

## Connectivity

### Connection

- PCIe x4
- Compatible with PCIe 1.1, PCIe 2.0 and PCIe 3 slots

## Certification/Compliance

### Emissions

- FCC Class B

### Environmental

- RoHS II (pending)
- REACH

## Physical Specifications

### Form Factor

- PCIe Add-In Card (Standard Height; Half Length)

### Weight

- < 500 g

### Dimensions

- Width: 111,15 mm
- Height: 18,6 mm
- Depth: 167,65 mm (excluding brackets)

## Operating Environment

### Temperature

- Operation: +10°C to +40°C (+50°F to +104°F)
- Storage: -10°C to +55°C (+14°F to +131°F)

### Relative Humidity

- 10% to 95% Non-condensing

## Electrical and Heat Specifications

### Operating Voltage

- 12 V supplied by PCIe Connector
- 3,3 V supplied by PCIe Connector

### Heat Dissipation

- Max. 85.3 BTU/h

## EMEA

### UTIMACO IS GmbH

Germanusstraße 4  
52080 Aachen,  
Germany

+49 241 1696 200

gamechanger@utimaco.com

## Americas

### UTIMACO Inc.

900 E Hamilton Ave., Suite 400  
Campbell, CA 95008,  
USA

+1 844 UTIMACO

gamechanger@utimaco.com

## APAC

### UTIMACO IS Pte Limited

50 Raffles Place,  
Level 19, Singapore Land Tower,  
Singapore 048623

+65 6631 2758

gamechanger@utimaco.com

For more information  
about UTIMACO HSM products,  
please visit:

[utimaco.com](http://utimaco.com)